


- 1/2" NPT
- Brass Body
- 2-Way Piloted Diaphragm
- Normally Open




Materials	Seals:	Nitrile, Viton®, Ethylene Propylene
	Orifice:	Pilot: Brass Main: Brass Ø 9/16"
Electrical	Standard Housing:	Encapsulated Waterproof Conduit (NEMA 4/4X)
	Optional Housings:	Metallic Conduit, Explosion-proof (NEMA 7), Grommet, Open Frame, Junction Box (single or dual knockouts), DIN; Contact GC Valves Customer Service for others.
	Standard Voltages:	24, 120, 240 AC 60 Hz; 50 Hz available 6, 12, 24 DC; Contact GC Valves Customer Service for Additional Voltages.
	Voltage Tolerance:	±10% of applicable voltage
	Coil Classes:	F, H, N
	Standard Lead Length:	24 inch
Operating Temperature	Ambient (Nominal):	32°F to 125°F
Mounting	Position:	Any
Approvals*	Agency:	UL Recognized, CSA Approved

* Not available for all variations

® Registered Trademark of DuPont Co.

Dimensions/Weight

Weight (lbs.)
2.5







S712 – 1/2" NPT, Brass Body, Normally Open

Valve Selection List


Normally Open



Energized



De-Energized



Pipe Size NPT	Orifice Size IN	C _v	Minimum	Operating Pressure Differential (psi)								Max Fluid Temp. °F	Seal Material	Power Consumption (Watts)		Model Code (120V/60HZ — 110V/50HZ Shown)
				Maximum										AC	DC	
				Air/Gas		Water		Light Oil		Steam*						
				AC	DC	AC	DC	AC	DC	AC	DC					
1/2	1/2	4.5	7	200	150	225	150	--	--	--	--	295	EPR	9	8	S712GF02C9DG1
	1/2	4.5	7	200	150	225	150	150	100	--	--	180	Buna	9	8	S712GF02N9DG1
	1/2	4.5	7	200	150	225	150	150	100	--	--	230	Viton	9	8	S712GF02N9DG1

* Class H Coil Recommended for High Temperature Applications

Part Numbering

1	2	3	4	5	6	7	8	9	10	11	12	13
S	7	1	2	G	F	0	2	N	9	D	G	1
Series			Operating Mode	Housing*	Coil Class*	Voltage*		Seal Material	Body Material	Pipe Connection	Orifice Size	
S11			2: Normally Open	G: Conduit	F: Class F H: Class H	02: 120/60 110/50		C: EPR N: Nitrile V: Viton	J: Brass	D: 1/2" NPT	GF: F/G'	

* See the "Engineering Guide" for additional voltages, variations and options.

Coil Data

Coil Family	
Type	Size
ALL	SH

Frequency (Hz)	60	50
Nominal Power (VA)	Inrush	36
	Holding	19

GC Valves Customer Service: 800-828-0484 (7:30am to 4pm ET) or 800-582-4232 (7:30am to 4pm PT)